SES STANDARD UNIT BUILDING

А

'DESIGN A1'

Coonamble SES Unit

FINISHES & FIXTURES SCHEDULE

Prepared by:



Date	Issue	Prepared	Checked/Approved
04/08/2021	A: Draft Issue	KM	

Table of Contents

1.0	GENERAL NOTES	3
1.1	AMENDMENT SUMMARY	3
2.0	EXTERIOR FINISHES	3
3.0	INTERIOR FINISHES	6
4.0	SANITARY FIXTURES	. 12
5.0	WHITEGOODS	. 19
6.0	GENERAL FIXTURES	.21
7.0	FURNITURE	.24
-		

1.0 GENERAL NOTES

- All sample images are indicative only.
- Refer to product trade literature for more accurate representations.
- Refer also Design Plans for additional details and setouts.
- For fixtures that are required to be in accordance with AS1428.1, their accurate setout and installation shall be the responsibility of the Builder.
- Provide coloured cold water and warm water indicator buttons to all taps.
- The Builder/contractor shall cross check all carpet and vinyl selections, ensure that they meet the requirements of Spec C1.10 of the BCA (fire hazard properties) and provide a compliance certificate upon completion.

The Builder shall cross check and confirm numbers of all items.

1.1 AMENDMENT SUMMARY

- A Draft Issue
- B Draft Issue
- C Final Draft Issue
- D Tender Issue
- E Coonamble Project

2.0 EXTERIOR FINISHES

Sample	Type/Location(s)	Name/Spec	Notes
SHALE GREY™ SA = 0.43. BCA = M	Colorbond cladding	Colorbond corrugated sheet cladding. Profile: Multiclad Sheet thickness: 0.42 BMT Colour: Shale Grey RGB 189 191 186 LRV value: 51	Provide neat. folded flashings (with safe edges) to all external corners, windows & other trim where required. Provide a proprietary colorbond edge trimmer to base of wall sheets. Extend min. 50mm down past slab edge FFL and provide continuous vermin proofing.
	Colorbond roofing and downpipes	Colorbond corrugated sheet roofing. Profile: Custom Orb Sheet thickness: 0.48 BMT	Provide neat. folded barge cappings (with safe edges) to all gables. Provide colorbond ridge cappings.

SHALE GREY™ SA = 0.43. BCA = M	Colorbond rotary roof vents.	Downpipes: 100mm dia. circular, with proprietary pre- fabricated elbows. Roof vents: Equal to CSR Edmunds 300mm aluminium, with colour to match roofing. Colour to all: Shale Grey	All trim to match roofing colour.
DEEP OCEAN® G SA = 0.75. BCA = D	Colorbond fascias, barges, gutters	Fascia & barge: Equal to colorbond steel Novaline. Gutters: 150mm half round & brackets to suit.	Roofing contractor to assess/review roof area, catchment & rainwater load calculations & ensure all installations meet Australian Standards.

Sample	Type/Location(s)	Name/Spec	Notes
SHALE GREY™ SA = 0.43. BCA = M	Colorbond eave soffit lining.	Colorbond corrugated sheet soffit. Profile: Mini Orb Sheet thickness: 0.42 BMT Colour: Shale Grey	
DEEP OCEAN® 9 SA = 0.75. BCA = D	Colorbond roller doors	Colour: Deep Ocean RGB 54 65 82 LRV value: 10	
	Colorbond sheet	Colour: Deep	Adhesive fix to
	facing to exterior egress doors	Ocean	flush face, exterior grade solid core

DEEP OCEAN® G SA = 0.75. BCA = D		Sheet thickness: 0.42 BMT	doors.
DEEP OCEAN® © SA = 0.75. BCA = D	Aluminium framed windows & glazed entry door unit. Frames & sashes/leafs.	Powdercoat finish. Colour: to match colorbond 'Deep Ocean'	
Sample No sample	Type/Location(s) Exterior concrete pavements, pathways &	Name/Spec Standard grey concrete.	Notes Ensure AS1428.1 compliant wheelchair persons
	driveway.	Broom, non-slip finish.	access is provided from site boundary (& access car space if provided) to front entry door.
	Colorbond rainwater tank.	Colorbond rainwater tank. Round, 20,000 litre capacity.	Set tank on RC slab, to engineers detail.
SHALE GREY™ SA = 0.43. BCA = M		Colour: Shale Grey	
	Steel bollards	Colour: Shale Grey 200mm dia. steel bollards, hot dip galv and gloss paint finish. Colour: To match 'SES orange'.	Confirm with client for exact paint colour specs. Builder to refer copy of SES Logo Specification Sheet.
	Steel bollards	200mm dia. steel bollards, hot dip galv and gloss paint finish. Colour: To match	for exact paint colour specs. Builder to refer copy of SES Logo Specification

	feature SES panel	on galv. steel frame. Colour: To match 'SES orange'. Colour: To match 'SES blue'.	for exact paint colour specs. Builder to refer copy of SES Logo Specification Sheet.
SES orange, PMS 1595		Colour: To match 'SES white'. (confer with client)	Builder to issue shop drawings and all details for proposed signage to client for approval prior to fabrication.
SES blue, PMS 288			
White sample not shown			

3.0 INTERIOR FINISHES

Sample	Type/Location(s)	Name/Spec	Notes
	Vinyl flooring, general areas: Option 1 - Kitchen - Lockers	Armstrong Accolade Plus Vinyl floor sheeting Colour: Mallee Wheat R10 slip resistance	Install in accordance with manufacturers specification.
Ceduna White	Vinyl flooring, wet areas: - Bathrooms	Armstrong Accolade Safe Wet area, textured vinyl floor sheeting Colour: Ceduna White R10 slip resistance	Install in accordance with manufacturers specification. Turn up walls to form 150mm tall coved skirting. Include a solid cove fillet.
Darling Grey	Vinyl flooring, wet areas: - Ldy - Cleaner	Armstrong Accolade Safe Wet area, textured vinyl floor sheeting Colour: Darling Grey R10 slip resistance	Install in accordance with manufacturers specification. Turn up walls to form 150mm tall coved skirting. Include a solid cove fillet.

Note: For all Armstrong Accolade vinyl products – Critical Radiant Flux \ge 8kW/m2 Smoke development rate \le 750% minutes

Sample	Type/Location(s)	Name/Spec	Notes
	Carpet:	Feltex Kokoda	Carpet style:
The second se	Option 2	carpet tile,	Level Loop Pile
		500 x 500mm	
	-		Fibre: Nylon
	Training/Operations	Colour:	
WIND PLAN AND	Room:	5500 Track	Carpet protection: Anti-static
A CONTRACT OF CONTRACTOR AND		Gauge:	Stain Resistance
		1/10th inch	Stainguard
The second se		Weight:	Flammability (AS
の「「「「「「「」」」」		575g/m2	ISO 9239.1.2003)
		····	CRF 9.8kW/m ²
			Smoke Value 79%
			Minutes
No sample	Concrete floor finish,	Steel float finish,	Floor / wall coating,
No sample	interior:	with clear sealer.	economical, water
		with clear sealer.	based epoxy,
	- vehicle bay	Sealer equal or	chemical resistant.
	- alcove areas	similar to :	
	outside of	Parchem	To provide a dust-
	bathrooms etc.	Nitoflor FC130	proof, easily
			cleaned surface
			which is resistant
			to most oils and
			liquids. It is suitable
			for use on walls
			and floors in
			warehouses,
			garages, light industrial and food
			processing areas,
			kitchens and other
			areas of pedestrian
			and light vehicular
			traffic.

Sample	Type/Location(s)	Name/Spec	Notes
	Sheet flooring: - over Hall, Store, Access WC & Cleaner's Rm in Vehicle Bay area	Eq to CSR yellow tongue particleboard sheet	
No sample	Skirting Option A: - general areas Pine skirting board	100x18mm DAR, square edge pine, with 5mm pencil round to leading, external edge Paint finish. Colour: to match door frames & leafs.	Note: A similar/slightly different sized profile may be nominated for the approval of the client.
No sample	Skirting Option B: NOT APPLICABLE - general areas a. Armstrong Feather Edge Skirting, 100mm Colour: Standard Midnight b. Armstrong Flat Skirting, 100mm Colour: Standard Midnight	Flexible vinyl skirting with a coved base (toe) and tapered top edge for use as a finish with smooth flooring. Available in 100mm and 150mm height and 1.5mm thick. All sizes in 15 metre coils. Flat, flexible vinyl skirting with tapered edges for use with carpet installations or as kick plates on doors. Available in 100mm and 150mm height and 1.5mm thick. All sizes in 30 metre coils.	Select appropriate skirting type depending on adjacent floor finish. Install in accordance with manufacturers specification.

Sample	Type/Location(s)	Name/Spec	Notes
ब्या क्या त	Paint Option 2: Wall, Trim & Door Leafs paint. Walls	Paint finish: All internal plasterboard and FC sheet walls. Wall colour:	Note: No door architrave. Tuck wall sheeting behind steel door frame with a neat
	(wash & wear, low sheen)	Dulux Lexicon Half (LRV value 87)	finish.
Lexicon Half			
	Steel door frames & solid core internal door leafs. (gloss)	Trim & door leafs colour: Dulux Northern Sky (LRV value 16)	
Winter Palace			
	Vehicle Bay: - internal colorbond wall sheet areas.	Colorbond corrugated sheet cladding. Profile: Multiclad Sheet thickness: 0.42 BMT	Provide neat. folded trim (with safe edges) to all external corners, windows & other junctions where required.
SHALE GREY™ SA = 0.43. BCA = M		Colour: Shale Grey RGB 189 191 186 LRV value: 51	

Sample	Type/Location(s)	Name/Spec	Notes
No sample	After Hours Delivery Bay: - internal security screen & sliding gate.	Galv. steel frame & chainwire infill.	Provide ceiling zone secure chainwire infill.
Ceduna White	Wet area wall sheeting: - bathroom basin splashbacks - shower alcoves - cleaner's room splashback - laundry splashback	Armstrong Accolade Standard vinyl floor sheeting, installed on wall Colour: Ceduna White	Provide a flush welded joint at junction of upturn coved vinyl skirting. Provide welded joints at internal corners.
No sample	Ceilings	Paint finish Colour: standard ceiling white	
	Kitchen joinery: - skirting	Laminate finish Laminex Colour: Charcoal, natural finish	Note: The builder shall submit shop drawings of all joinery items to the client for approval, prior to fabrication.
	Kitchen joinery: - drawer & cupd door faces - pelmet to o'head cupds - cupd door faces to UPS, ICT rack & store adjacent bathrooms	Laminate finish Laminex Colour: Bleached Elm, natural finish	Note: all interiors of joinery to be finished in white melamine.

Sample	Type/Location(s)	Name/Spec	Notes
	Kitchen joinery: - benchtop - splashback Other shelf items: - shelf in access bathroom - shelf in after hours delivery bay	Laminate finish Formica Colour: Ice Quarstone, velour finish	Finish benchtop with a rounded, laminate bullnose to leading edge.
	Kitchen joinery - cupd door & drawer handles	Satin finish SS D-Pull handles, 100mm.	
No image	ICT Rack Cupd adjacent to kitchen joinery	Provide laminate cupd doors, with al. vent panels located at lower level. All possible vermin proofing to be taken into consideration Cupd space: 1200w x 1200d	Interior of cupd space to be set plaster'bd, painted. Provide shop drawing for client review.
No image	Laundry – Folding bench portion	Provide a laminate finish folding bench in the position noted on the plan. Approx: 800l x 450d mounted to the side wall and positioned to fold over and rest on the tub edge, with rubber feet. Laminate colour to match kitchen benchtop.	Site measure. Provide wall stay hook for the 'up position'. Lightweight for easy operation, with sturdy piano hinge and wall mounting plate over nogging. Provide shop drawing for client review.

Sample	Type/Location(s)	Name/Spec	Notes
No image	Store Room –	Provide a laminate	Provide shop
	Bench & shelving	finish bench with	drawing for client
		open, adjustable	review.
		shelving under.	
			Bench: 600 deep x
		Provide 2 x laminate	width of room.
		finish shelves over	
		bench, mounted on	Benchtop set at

	steel p'coat brackets/runners. Laminate bench colour to match kitchen benchtop.	900 AFL. Shelves: 300 deep x width of room.
UPS Cupd adjacent to female locker room	Provide solid core cupd doors, painted, with al. vent panels located at lower level.	Interior of cupd space to be set plaster'bd, painted.
	All possible vermin proofing to be taken into consideration Cupd space: 1130w x 1300d	
t	o female locker	JPS Cupd adjacent o female locker oomProvide solid core cupd doors, painted, with al. vent panels located at lower level.All possible vermin proofing to be taken into considerationCupd space:

4.0 SANITARY FIXTURES

Sample	Type/Location(s)	Name/Spec	Notes
	Kitchen - sink	Base Mk3 single bowl (LH), single tap hole	
	Kitchen - flickmixer	Posh Bristol Mk2 sink mixer (4 star)	
E.	Access Bathroom - hand basin	Caroma Cosmo wall basin	Install pvc waste pipe with 'knee room' clearances to AS1428.1 Set basin at correct height & position to AS1428.1
	Access Bathroom - flickmixer	Caroma Acqua Care basin mixer	

Access Bathroom: - toilet suite	Caroma Care V2 Connector Suite with backrest & grey toilet seat.	Install to AS1428.1 setouts.

Sample	Type/Location(s)	Name/Spec	Notes
	Male/Female	Caroma Slimline	
	Bathrooms:	Concorde	
	- toilet suite	Connector Suite,	
		with Tasman seat &	
		cover	
No image	All toilets (x3):	Standard style	
	 cistern cock 	cistern cock &	
		chrome finish pipe	
		to cistern.	
		Duble 1	
		Bright chrome	
		finish.	
	Male/Female	Victoria Wall Basin,	Install with neat
	Bathrooms:		
	- hand basin	520mm, 3 taphole, white china.	pvc waste.
* 1		white china.	
at sit we			
•			
		Bunnings	
я		Cibo Design 600mm	
		White	
0		I/N 4844253	
		1/11 TOTT200	
-			
	Male/Female	Posh Bristol, Basin	Provide coloured
	Bathrooms:	Tapset, swivel type,	tap caps for
3	- hand basin tapset	chrome finish.	hot/cold.
	All Bathrooms	Lenlok toilet paper	Install to AS1428.1
	 toilet paper holder 	holder, satin finish	setout for access
		aluminum	bathroom.
3			
all a			
1		1	

Sample	Type/Location(s)	Name/Spec	Notes
	Access Bathroom - grab rail 1	Caroma Virtu Comfort grab rail, 960x600mm, 90 deg vertical 32mm dia. brushed ss finish Select left or right hand to suit WC layout.	Install to AS1428.1 setout for access bathroom.
	Access Bathroom - grab rail 1	Caroma Virtu Comfort grab rail, 300mm 32mm dia. brushed ss finish	Install to AS1428.1 setout for access bathroom.
	Ambulant WC grab rails - male/female bathrooms	Caroma Virtu Comfort grab rail, 450x450mm, 90 deg vertical 32mm dia. brushed ss finish 2 x rails per WC, left & right hand.	Install to AS1428.1 setout for ambulant WCs.
	Bathrooms: - robe hooks	Base Robe Hook, chrome finish	Allow for 1 x robe hook per bathroom. Confirm position with client prior to installation. Install to AS1428.1 setout for access WC.
6	Male/Female Bathrooms: - towel rail	Base Towel Rail, 800mm long, chrome finish.	Allow for 1 x towel rail each for male & female bathroom. Confirm position with client prior to installation.

	1
	1
	i

Sample	Type/Location(s)	Name/Spec	Notes
No sample	Male/Female Bathrooms: - shower rod & curtain	Provide a simple, chrome finish curtain rod & curtain to each shower. Builder to nominate curtain type & colour for client approval prior to installation.	
	Male/Female Bathrooms: - shower set	Posh Bristol lever shower set, chrome finish.	
	Male/Female Bathrooms: - soap holder inside shower alcove	Caroma Cosmo soap holder, chrome finish.	Confirm position with client prior to installation.
No sample	All bathrooms: - wall mirror	Provide a mirror, with white powdercoat al. frame, 1000x600mm to each bathroom. Locate as vertical rectangle over hand basin.	Install to AS1428.1 setout for access WC.
	All bathrooms: - soap dispenser	Tork Liquid Soap Dispenser, white. No. 560000 Confirm position(s) with client prior to installation.	Provide also 1 x soap refill per unit. Mount adjacent each hand basin. Install to AS1428.1 setout for access WC.

Sample	Type/Location(s)	Name/Spec	Notes
	All bathrooms: - paper towel holder	Tork Xpress Multifold Hand Towel Dispenser, white.	Provide also 1 x packet of single ply hand towels per holder.
ø		No. 552030	Mount adjacent each hand basin.
		Confirm position(s) with client prior to installation.	Install to AS1428.1 setout for access WC.
	All bathrooms: - plastic waste bin, small	Willow Swing & Stay, plastic bin, 25L, off white.	1 x bin per bathroom. Available at
			Bunnings.
al hard marked	Access WC: Thermostatic mixing valve (TMV)	Equal or similar to: Enware Aquablend 2000 ATMS 216E	Located in a recessed, lockable stainless steel wall cabinet.
	This unit supplies controlled hot water to the Access WC	Connect to HWS, as required.	Make face of cabinet flush with finished wall.
	hand basin.		Position cabinet in a convenient, accessible location.
	Laundry: - washing machine set	Posh Bristol lever taps, chrome finish	
Re Contraction of the contractio			

Sample	Type/Location(s)	Name/Spec	Notes
	Laundry:	Posh Bristol lever	
	- laundry tub set, wall mounted	taps, chrome finish	
		and	
	and		
		Laundry Arm,	
	Cleaner's sink	300mm standard,	
	- spout & tapset,	chrome finish	

	wall mounted		
17 Tb	Laundry: - tub/sink	Posh Solus 45L	
	Sink with bench and Under shelving	standard trough & cabinet, with bypass. 500w x 610d x 875h	
	Cleaner's Room: wall mounted broom holder	Oates 5 handle storage holder. 1 off unit 700mm long.	Available at Bunnings Mount on wall, inside Cleaners Room, to position confirmed by client. Provide a nogging in wall frame.
	Cleaner's Room: - cleaners sink	Wolfen stainless steel cleaners sink, with grate, 35L. 555w x 455d	Install neat pvc waste.
	TAP STYLE - OPTION 2 Lever Style tap option for the following tap sets: - basins to M and F bathrooms - M & F showers	Posh Bristol Lever Wall Top Assembly Ceramic Disc Chrome finish	Note: This style tap may be selected in lieu of all capstan style taps listed in this schedule. Client to advise if applicable for a particular project.

- washing machine - laundry tub - cleaner's sink		
--	--	--

* Note all fittings for the proposed Access WC are subject to review and approval of the Certifying Authority, prior to construction.

Sample	Type/Location(s)	Name/Spec	Notes
	Vehicle Bay: - H2O station	Aquacooler M3F Drinking Fountain Filtered Dark grey powdercoat finish (model suited for 0-15 people, office type)	Provide power and water supply/drainage.
	Roof: - HWS	Solahart 302J 300 litre Roof Top Solar System	Note: The Solahart 302J solar water heater is specifically designed to provide economical service in medium to high solar gain areas, and is suitable for frost prone or harsh water chemistry areas. Provide also electrical backup power switch.

5.0 WHITEGOODS

Sample	Type/Location(s)	Name/Spec	Notes
	Kitchen:	Westinghouse	Greenhouse and
	- fridge	WBE4500WC	Energy Minimum Standards (GEMS)
		453L Bottom Mount	_ ```
		Refrigerator	Refrigerator/Freeze rs – at least 3.5
		699W x 723D x 1725H	stars
		Left side handle	

Kitchen: - cooker	Westinghouse WLE525WB 54cm freestanding cooker with coil hob and fan forced oven 540W x 620D x	
Kitchen: - range hood, pull out type	1150H Westinghouse WRH608IW Slide-out Rangehood 599W x 300D x 175H	Connect duct exhaust to external wall (via ceiling space) with discreet louvre panel.
Laundry: - washing machine	Simpson SWT7055LMWA 7.0kg EZI Set top load washer 575w x 642d x 975h	Greenhouse and Energy Minimum Standards (GEMS) – Washing Machines – at least 3.5 stars
Microwave Reverse Cycle Air Conditioners	Good Guys – Dubbo (May deliver) Samsung 40L 1000W Stainless Steel 555wx313hx439d WTZ ME6144ST	\$250.00 Greenhouse and Energy Minimum Standards (GEMS)

Air-to-air heat pumps and air- conditioners – 4 stars if less than 4kW and 3 stars if greater that 4 kW (applies to both heating and coolong for reverse
conditioners)

6.0 GENERAL FIXTURES

Sample	Type/Location(s)	Name/Spec	Notes
	Vehicle Bay: - racking	Dexion Speedlock shelving, 4 tier, 2400 high, 600 deep. 3 off 2400 x 600 modules (vehicle Bay) 1 off 1800 x 600 module (vehicle bay/ameneties entry)	Supply with timber or mesh shelves, as per client preference.
Bigging 250 mm Bigging 250 mm Specifick mobile work bench. 75 Open beams with particle board work surface and bottom shelf & castors.	Vehicle Bay: - work bench	Dexion Speedlock mobile work bench 930x838x2591mm With Castors	
	Vehicle Bay: - vehicle wheel stops	Blackwoods Wheel Stop Polite Enterprises (for concrete surface with 3 concrete screw anchors (sold separately)) Solid Recycled Plastic Store/boat shed	1650mm \$116 each N <mark>ot required due to</mark> multiple vehicles parking

		Product # 01047208	
RS PRO 11m 0 Socket 10A Extension Reel With Auto R IP42 RS Stock No: 284 9748 Manufacturer (RS PRO)	Drop down retractable electrical leads	Shore Power Reels The standard shore power supply used in NSW SES facilities is RS PRO 11m 10A 230V Extension Reel with Auto Rewind.	Will require connection to 240v power supply \$290 each Installation Notes: Power Reels are to be situated 3 metres from the front of the building on the driver's side of the vehicle
	Picker	Platform Step Ladder, 3 step, 150kg rating Blackwoods Baileys FS13874 Mobile Order Picker temporary work platform 3 MK3 Aluminium, product # 01497415	\$2289 gst inc SES to supply
No sample	UPS	Fixed into UPS cupboard space,	15 amp, 30 mins or more of back up power
T00076 with optional timer.		Birko 5 litre – or similar Wall mounted hot water for tea & Coffee	Will need to be plumbed in. To be mounted onto the wall in the kitchen, above the sink drainage

Sample	Type/Location(s)	Name/Spec	Notes
	Vehicle Bay:	Hazmat Safety	Refer floor plan for
	- Hazmat cabinet	Cabinets	location.
		<u>or Equivalent</u>	

REMAINED BARNESS		<mark>160L model</mark> MHFC-0160 1100w x 450d x 1220h	
Image: Construction of the second	External Gas Cage Gas Cage, 2 x 9kg gas bottle storage	Blackwoods Spill Crew BW#: 04197053 620h x 825w x 435d Blue powedercoat steel construction. <u>or Equivalent</u> Set cage on 100mm reinforced concrete plinth, sized to match.	Locate gas cage in an external location as agreed with the client. Gas cage to be located a min. 3.0m away from any ignition source.
	Vehicle Bay: - general purpose hanging wall rack	Equal or similar to Australian Steel & Wire Weld Mesh Industrial Standard Galvanized Sheet 4 x panels, 2.4m x 1.2m 50/50 4mm	Install/fix to vehicle bay wall framing with additional timber studs, as required. Mount at height as directed by client.

7.0 FURNITURE

Sample	Type/Location(s)	Name/Spec	Notes
	Cleaner's Room Shelving Unit 1 off	Q Office Go Wardrobe Unit 2100hx910wx450d (Cleaners cupboard, lockable)) silver grey	
Sample	Type/Location(s)	Name/Spec	Notes
	Office	Q office Fundamentals Desk 1795W x 900D x 725H Cable Port Drilled Centre/Rear FMDSKST1890	@ \$400 each Need 2 for the Office Add \$20 each for 80mm cable ports
	Training/Operatio ns Room: - tables	Q office Host flip table frame 1800 X 650 TO 2100 X 1000 DDKIMHOFTB18 Fundamentals Top 2100 X 900 X 25MM FMTOP25REC2190 CABLE ENTRY PORT 80MM DRILLED CENTRE/ REAR OF ABOVE TOPS FMXCAP80 Flip table links to suit DDKIHTTCOLA	\$382.73 each x 2 \$260.91 each x 2 \$20 each x 2 34.55 each x 2
	Training/Operatio	Q office	

ns Room: - chairs for centre tables	Yarra mesh back chair, black fabric seat	10 training room, 2 for office \$224.55 each
Training/Operatio ns Room: - mobile pedestal file drawer	Q office Fundamentals Mobile Pedestal 2 Pen + 1 File Drawer Lockable 480W X 520D X 690H FMMPD6902P1F FMXBARLOCK	\$313.64 Lock fitted to drawer if required @\$59.09
Training/Operatio ns Room: - filing cabinet, 3 drawer	Q office GO STEEL 3 DRAWER FILING CABINET FURGFCA3W	\$300
Accom modate PA system (radio rebroadc ast) Drawers Office	Q office Custom Pedestal 1 Pen + 1 File Drawer Open Shelf to Accommodate PA Syst Lockable PD-0321_037	\$394.54 FUNDAMENTALS CUSTOM PEDESTAL 480W X 520D X 690H. OPEN TOP SECTION WITH NO BACK - TO FIT PA (430W X 360D X 150H)
Training operations & Office Credenza (printer on top in office)	Q office FUNDAMENTAL SLIDING DOOR CREDENZA 1800W X 450D X 900H FMCRS184590 Lock fitted if required FMXSLIDELOCK	\$740.00 x 2 1 x Office 1 x Training room \$50.91 x 2 (If required)

Lockers	Q office Statewide 2 Door Step Locker 1800H x 380W x 450D Key Locking STASSLW	Male and Female bathrooms \$340 each x 14
Locker stand/bench	Q office Statewide Locker Stand with Bench Seat 450mm Seat Height Modwood Seat Slats STATEWIDE LOCKER STAND/SEAT TO SUIT BANK OF 2 STEP LOCKERS. STEEL CONSTRUCTION WITH	To fit above 14 lockers, 7 in mens and 7 in female bathrooms \$494.55 x 4
	MODWOOD SEAT SLATS STASLSEATS TANDMW380-2 STATEWIDE LOCKER STAND/SEAT TO SUIT BANK OF 3 STEP LOCKERS. STEEL CONSTRUCTION WITH MODWOOD SEAT SLATS STASLSEATS TANDMW380-3	\$554.55 x 2

8.0 Audio Visual Display

75" ↓	AV – 75 inch Smart TV	With Wall bracket	NSW SES to procure Connect to TV aerial/antenna Approx. \$3000 Ensure studs are adequate for mounting bracket
	Camera webcam Sound bar?	https://www.logit ech.com/en- au/products/vide O- conferencing/conf erence- cameras/meetup- conferencecam.96 0-001101.html	NSW SES to procure approx. \$1300
	Laptop – PC	TBC DL	\$780 NSW SES to purchase plus additional software cost approx. \$350
	Monitors - duel	Dell 24" Monitor (P2421D)	Dell Agreement
	1.5m HDMI cable for dual monitors	1.5m x 2	